



PROGEF Standard Manchon union SDR11/PN10

Exécution:

- Matériau: PP-H
- IR = Compatible soudure infra rouge
- Soudage conventionnel bout à bout selon DVS 2207

Avec bouts mâles pour soudage bout à bout
joint: joint torique EPDM

Pour les dimensions d75-110, merci de consulter les instructions de montage
d75-d110 nouvelle conception de filetage depuis 2022

d (mm)	SDR	PN (bar)	MDS	EPDM Code	CAN	FKM Code	CAN	Poids (kg)
20	11	10	IR	727 518 506		727 528 506		0.047
25	11	10	IR	727 518 507		727 528 507		0.072
32	11	10	IR	727 518 508		727 528 508		0.100
40	11	10	IR	727 518 509		727 528 509		0.145
50	11	10	IR	727 518 510		727 528 510		0.190
63	11	10	IR	727 518 511		727 528 511		0.332
75	11	10	IR	727 518 212		727 528 212		0.520
90	11	10	IR	727 518 213		727 528 213		0.533
110	11	10	IR	727 518 214		727 528 214		0.754

d (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	D (mm)	G (inch)	e (mm)	Dimension	O-Ring EPDM
20	107.0	54.0	53.0	26	37	48	1	1.9	20,22 x 3,53	748.410.006
25	113.0	57.0	56.0	26	36	58	1 1/4	2.3	28,17 x 3,53	748.410.007
32	119.0	60.0	59.0	26	25	65	1 1/2	2.9	32,93 x 3,53	748.410.008
40	126.0	63.0	63.0	26	25	79	2	3.7	40,65 x 5,34	748.410.009
50	131.0	65.5	65.5	26	25	91	2 1/4	4.6	46,99 x 5,34	748.410.010
63	137.0	69.0	68.0	26	26	111	2 3/4	5.8	59,69 x 5,34	748.410.011
75	134.5	68.5	66.0	26	34	138	S110x5	6.8	66,04 x 5,33	748.410.024
90	134.5	68.5	66.0	26	45	138	S110x5	8.2	74,63 x 5,34	748.410.383
110	139.5	74.0	65.5	33	40	161	S130x5	10.0	94,62 x 5,34	748.410.248

d O-Ring FKM

d (mm)	
20	749.410.006
25	749.410.007
32	749.410.008
40	749.410.009
50	749.410.010
63	749.410.011
75	749.410.024
90	749.410.383
110	749.410.248

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>