



PROGEF Standard 变径 S8.3/SDR17.6

型号:

- 材质：PP-H
 - 传统对焊符合DVS 2207
 - IR红外焊兼容 焊接参数：PP-H
- 1 材质：PP-R

d	d1	FM	code	SP	weight	L	L1	L2	e	e1	
(mm)	(mm)				(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	
50	40	IR	727 908 949	5	0,010	55	12	12	2,9	2,3	
63	40	IR	727 908 901	10	0,020	65	16	12	3,6	2,3	
63	50	IR	727 908 900	10	0,020	65	16	12	3,6	2,9	
75	40	IR	727 908 904	10	0,041	65	20	20	4,3	2,3	
75	50	IR	727 908 465	10	0,047	65	20	20	4,8	3,2	
75	63	IR	727 908 464	10	0,053	65	20	20	4,3	3,6	
90	63	IR	727 908 471	20	0,079	75	22	19	5,1	3,6	
90	75	IR	727 908 470	12	0,090	75	21	19	5,1	4,3	
110	63	IR	727 908 472	8	0,149	90	28	28	6,9	4,0	
110	75	IR	727 908 477	8	0,149	90	28	18	6,3	4,3	
110	90	IR	727 908 476	10	0,158	90	28	20	6,3	5,1	
125	110	IR	727 908 912	12	0,190	108	32	28	7,1	6,3	
140	110	IR	727 908 917	8	0,322	115	35	28	8,0	6,3	
140	125	IR	727 908 916	8	0,353	115	35	32	8,0	7,1	
160	110	IR	727 908 922	4	0,454	124	40	28	9,1	6,3	
160	140	IR	727 908 920	2	0,482	124	40	35	9,1	8,0	
180	90	IR	727 908 928	2	0,866	157	45	22	10,2	5,1	
180	110	IR	727 908 927	2	0,698	157	45	28	10,2	6,3	
180	125	IR	727 908 926	2	0,596	136	45	32	10,2	7,1	
180	140	IR	727 908 925	2	0,632	136	45	35	10,2	8,0	
180	160	IR	727 908 924	2	0,677	136	45	40	10,2	9,1	
200	160	IR	727 908 930	2	0,805	151	50	40	11,4	9,1	
200	180	IR	727 908 929	2	0,895	151	50	45	11,4	10,2	
225	110	IR	727 908 936	2	1,001	171	55	40	12,8	6,3	
225	160	IR	727 908 934	2	1,082	171	55	45	12,8	9,1	
225	180	IR	727 908 933	2	1,337	171	55	45	12,8	10,2	
225	200	IR	727 908 932	1	1,184	184	60	40	12,8	11,4	
250	160	--	727 908 940	1	2,062	194	60	40	14,2	9,1	
250	225	--	727 908 937	1	1,792	182	60	55	14,2	12,8	
1	280	225	--	727 908 942	1	1,365	105	30	20	15,9	12,8
1	280	250	--	727 908 941	1	0,858	70	30	18	15,9	14,2
1	315	225	--	727 908 947	1	2,062	130	30	20	17,9	12,8
1	315	250	--	727 908 946	1	1,578	100	30	20	17,9	14,2
1	315	280	--	727 908 945	1	1,156	63	30	18	17,9	15,9
1	355	250	--	727 908 959	1	3,000	245	90	60	20,1	14,2
1	355	280	--	727 908 958	1	2,700	245	90	70	20,1	15,9
1	355	315	--	727 908 957	1	2,400	245	90	80	20,1	17,9
1	400	315	--	727 908 972	1	3,600	260	95	80	22,7	17,9
1	400	355	--	727 908 971	1	3,100	260	95	90	22,7	20,1
450	280	--	727 908 967		6,000	230	60	70	25,5	15,9	
450	315	--	727 908 984	2	5,400	230	60	80	25,5	17,9	
450	355	--	727 908 988		5,000	230	60	90	25,5	20,1	
450	400	--	727 908 989	1	5,000	230	60	95	25,5	22,7	
500	315	--	727 908 993		8,100	230	60	80	28,4	17,9	
500	355	--	727 908 994		7,300	230	60	95	28,4	20,1	
500	400	--	727 908 998	1	6,700	230	60	95	28,4	22,7	
500	450	--	727 908 999	2	5,500	230	60	60	28,4	25,5	

Data sheet

valid from: 2024/8/1



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>