



ELGEF Plus Collier de dérivation PE100 d110-250mm / SDR11 / Sortie d90-125 mm

- 5 bar gaz / 16 bar eau
 - Collier de dérivation complet, avec selle inférieure et 3 vis
 - Préfixation avec charnière clips
 - Raccordement électrosoudable avec système de fixation intégré
 - Élément chauffant protégé de tout contact avec le fluide
 - Connecteurs 4 mm
 - Indicateur de soudage
 - Approuvé FM 1613 – 15 bar
- * Livré sans partie inférieure. Fixation des tuyaux avec outil à usage multiple n° 193.281.027

d	d2	Di1	DN	PN	Code	CAN	Poids
(mm)	(mm)	(mm)	(mm)	(bar)			(kg)
110	65	90	100	16	193 135 009	461 377	1.124
110	65	110	100	16	193 135 010	461 417	1.224
125	65	90	100	16	193 135 019	461 378	1.134
125	65	110	100	16	193 135 020	461 418	1.290
* 140	65	90	125	16	193 135 029	461 381	0.982
* 140	65	110	125	16	193 135 030	461 421	1.087
160	65	90	150	16	193 135 039	461 382	1.449
160	86	110	150	16	193 135 040	461 422	1.582
160	86	125	150	16	193 135 041	461 432	1.782
180	65	90	150	16	193 135 049	461 383	1.672
180	86	110	150	16	193 135 050	461 423	1.765
180	86	125	150	16	193 135 051	461 433	2.015
200	65	90	200	16	193 135 059	461 384	1.803
200	86	110	200	16	193 135 060	461 424	1.963
200	86	125	200	16	193 135 061	461 434	2.128
225	65	90	200	16	193 135 069	461 385	2.006
225	86	110	200	16	193 135 070	461 425	2.400
225	86	125	200	16	193 135 071	461 435	2.312
250	65	90	250	16	193 135 079	461 386	2.145
250	86	110	250	16	193 135 080	461 426	2.258
250	86	125	250	16	193 135 081	461 436	2.500

d	Lmax	P1	W	H	Tube SDR
(mm)	(mm)	(mm)	(mm)	(mm)	
110	164	82	220	101	9-11
110	164	88	220	107	9-11
125	179	82	220	101	9-11
125	179	88	220	107	9-11
* 140	195	81	220	101	9-11
* 140	195	87	220	107	9-11
160	215	82	240	102	9-17.6
160	215	88	240	108	9-17.6
160	215	99	240	129	9-17.6
180	237	82	260	102	9-17.6
180	237	88	260	108	9-17.6
180	237	99	260	129	9-17.6
200	253	82	260	102	9-17.6
200	253	88	260	108	9-17.6
200	253	99	260	129	9-17.6
225	287	82	260	102	9-17.6
225	287	88	260	108	9-17.6
225	287	99	260	129	9-17.6
250	312	82	260	102	9-26
250	312	88	260	108	9-26
250	312	99	260	129	9-26

Data sheet

valid from: 24/01/2025



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>