



SYGEF Plus tee 90° reduced
SDR21/PN16
High Purity clean-room product ISO Class 5 (100)

	d - d1 (mm)	FM	Code	e (mm)	e1 (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)
A	63 - 20	BCF, IR	735 208 956	3.0	1.9	60	67	25	35
A	63 - 25	BCF, IR	735 208 957	3.0	1.9	60	66	25	34
A	63 - 32	BCF, IR	735 208 958	3.0	2.4	60	67	25	25
A	63 - 40	BCF, IR	735 208 959	3.0	2.4	60	66	25	26
A	75 - 20	BCF, IR	735 208 961	3.6	1.9	65	69	25	31
A	75 - 25	BCF, IR	735 208 962	3.6	1.9	65	72	25	34
A	75 - 32	BCF, IR	735 208 963	3.6	2.4	65	69	25	31
A	75 - 40	BCF, IR	735 208 964	3.6	2.4	65	72	25	26
A	75 - 50	BCF, IR	735 208 965	3.6	3.0	65	69	25	26
A	90 - 20	BCF, IR	735 208 967	4.3	1.9	65	76	25	31
A	90 - 25	BCF, IR	735 208 968	4.3	1.9	65	79	25	34
A	90 - 32	BCF, IR	735 208 969	4.3	2.4	65	76	25	31
A	90 - 40	BCF, IR	735 208 970	4.3	2.4	65	79	25	26
A	90 - 50	BCF, IR	735 208 971	4.3	3.0	65	76	25	26
B	90 - 63	BCF, IR	735 208 972	4.3	3.0	80	85	25	25
A	110 - 20	BCF, IR	735 208 974	5.3	1.9	65	86	25	31
A	110 - 25	BCF, IR	735 208 975	5.3	1.9	65	89	25	34
A	110 - 32	BCF, IR	735 208 976	5.3	2.4	65	86	25	31
A	110 - 40	BCF, IR	735 208 977	5.3	2.4	65	89	25	26
A	110 - 50	BCF, IR	735 208 978	5.3	3.0	65	86	25	26
B	110 - 63	BCF, IR	735 208 979	5.3	3.0	90	95	30	25
B	110 - 75	BCF, IR	735 208 980	5.3	3.0	90	95	30	25
B	110 - 90	BCF, IR	735 208 981	5.3	4.3	90	95	30	25
B	160 - 90	IR	735 208 687	7.7	4.3	155	130	60	25
B	160 - 110	IR	735 208 686	7.7	5.3	155	130	60	25
B	225 - 90	IR	735 208 695	10.8	4.3	155	160	60	25
B	225 - 110	IR	735 208 694	10.8	5.3	155	160	60	25

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
 info.ps@georgfischer.com Internet: <http://www.gfps.com>