




ecoFIT outlet flange adaptor PE100 d40-315mm / SDR11

Model:

- Suitable for wafer check valves Type 369
- Conventional butt-welding according to DVS 2207

Attention:

- In conjunction with Outlet flange adaptors, **flange rings for socket systems** must be used.

d	Di	DN	SDR	PN	Code	Weight	Lmax	D1	Q2	s2	r	b1	BD
(mm)	(mm)	(mm)		(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
40	37	32	11	16	733 808 034	0.073	64	80	30	3.7	3	11	50
50	43	40	11	16	733 808 035	0.104	67	90	30	4.6	3	12	61
63	54	50	11	16	733 808 036	0.172	74	105	30	5.8	4	14	76
75	70	65	11	16	733 808 037	0.242	78	125	30	6.8	4	16	90
90	82	80	11	16	733 808 038	0.348	87	140	35	8.2	4	17	108
110	105	100	11	16	733 808 039	0.508	102	160	41	10.0	4	18	131
140	130	125	11	16	733 808 041	0.976	124	190	47	12.7	4	25	165
160	158	150	11	16	733 808 042	1.337	149	215	52	14.6	4	25	188
225	206	200	11	16	733 808 045	2.814	180	270	55	20.5	4	32	248
280	259	250	11	16	733 808 047	4.374	240	325	63	25.4	4	35	308
315	308	300	11	16	733 808 048	4.960	272	375	66	28.6	4	35	346

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>