


Stellantrieb pneumatisch Typ PA 30 - PA 70 Federkraft schliessend/Federkraft öffnend (FC/FO)

*nur für Absperrklappe Typ 565

Typ	Code	NPK	SP	Gewicht (kg)
PA 30 FC	198 811 617		1	2.022
PA 30 FO	198 811 627		1	2.020
PA 35 FC	198 811 601		1	2.673
PA 35 FO	198 811 628		1	2.675
PA 40 FC	198 811 609		1	3.602
PA 40 FO	198 811 629		1	3.623
PA 45 FC	198 811 603		1	4.962
PA 45 FO	198 811 630		1	4.944
PA 50 FC	198 811 610		1	6.921
PA 50 FO	198 811 631		1	6.819
PA 55 FC	198 811 605		1	9.354
PA 55 FO	198 811 632		1	9.203
PA 60 FC	198 811 611		1	11.371
* PA 60 FC	198 811 652		1	11.371
* PA 60 FO	198 811 653		1	11.371
PA 65 FC	198 811 607		1	15.900
PA 70 FC	198 811 612		1	18.758
PA 70 FO	198 811 634		1	18.750

Typ	#	D1 (mm)	D2 (mm)	D3 (mm)	D4 (inch)	D5 (mm)	L (mm)	L2 (mm)	L3 (mm)	L6 (mm)	H (mm)
PA 30 FC	F05/07	50	70	M8x12	½	M6x9	274.4	14	70.4	10	98.2
PA 30 FO	F05/07	50	70	M8x12	½	M6x9	274.4	14	70.4	10	98.2
PA 35 FC	F05/07	50	70	M8x12	½	M6x9	325.2	17	83.3	12	111.1
PA 35 FO	F05/07	50	70	M8x12	½	M6x9	325.2	17	83.3	12	111.1
PA 40 FC	F05/07	50	70	M8x12	½	M6x9	359.5	17	87.0	12	114.8
PA 40 FO	F05/07	50	70	M8x12	½	M6x9	359.5	17	87.0	12	114.8
PA 45 FC	F07/10	70	102	M10x15	½	M8x12	418.0	22	107.5	15	149.5
PA 45 FO	F07/10	70	102	M10x15	½	M8x12	418.0	22	107.5	15	149.5
PA 50 FC	F07/10	70	102	M10x15	½	M8x12	433.9	22	111.1	15	153.1
PA 50 FO	F07/10	70	102	M10x15	½	M8x12	433.9	22	111.1	15	153.1
PA 55 FC	F07/10	70	102	M10x15	½	M8x12	498.3	22	118.0	19	160.0
PA 55 FO	F07/10	70	102	M10x15	½	M8x12	498.3	22	118.0	19	160.0
PA 60 FC	F10/12	102	123	M12x18	¾	M10x15	547.3	27	134.9	19	176.9
* PA 60 FC	F10/12	102	123	M12x18	¾	M10x15	547.3	27	134.9	19	176.9
* PA 60 FO	F10/12	102	123	M12x18	¾	M10x15	547.3	27	134.9	19	176.9
PA 65 FC	F10/12	102	125	M12x18	¾	M10x15	646.0	27	148.0	22	190.0
PA 70 FC	F10/12	102	125	M12x18	¾	M10x15	681.0	36	168.0	24	210.1
PA 70 FO	F10/12	102	125	M12x18	¾	M10x15	681.0	36	168.0	24	210.1

Typ	H1 (mm)	H2 (mm)	H3 (mm)	H5 (mm)	H6 (mm)
PA 30 FC	70.4	90.4	35.7	13.0	20
PA 30 FO	70.4	90.4	35.7	13.0	20
PA 35 FC	83.3	103.3	42.8	13.0	20
PA 35 FO	83.3	103.3	42.8	13.0	20
PA 40 FC	87.0	107.0	44.8	13.0	20
PA 40 FO	87.0	107.0	44.8	13.0	20
PA 45 FC	107.5	137.5	54.5	16.0	30
PA 45 FO	107.5	137.5	54.5	16.0	30
PA 50 FC	111.1	141.1	58.1	17.0	30
PA 50 FO	111.1	141.1	58.1	17.0	30
PA 55 FC	118.0	148.0	60.0	19.0	30
PA 55 FO	118.0	148.0	60.0	19.0	30



Typ	H1 (mm)	H2 (mm)	H3 (mm)	H5 (mm)	H6 (mm)
PA 60 FC	134.9	164.9	57.4	19.0	30
* PA 60 FC	134.9	164.9	57.4	19.0	30
* PA 60 FO	134.9	164.9	57.4	19.0	30
PA 65 FC	148.0	178.0	61.5	19.5	30
PA 70 FC	168.0	198.0	78.0	19.5	30
PA 70 FO	168.0	198.0	78.0	19.5	30

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>