




## PROGEF Standard Hydro-injecteur type P20

### Exécution:


- Matériau: PP-H
- DN 10-20: Filetage extérieur parallèle et emboîture pour soudage métrique avec O-Ring EPDM
- DN 25-50: Emboîture métrique à souder avec O-Ring EPDM
- DN 65-80: Embout métrique à souder sans O-Ring

| d    | DN   | Pouces | PN    | Code        | CAN | SP | Poids |
|------|------|--------|-------|-------------|-----|----|-------|
| (mm) | (mm) | (inch) | (bar) |             |     |    | (kg)  |
| 16   | 10   | 3/8    | 10    | 199 041 129 |     |    | 0.102 |
| 20   | 15   | 1/2    | 10    | 199 041 130 |     |    | 0.175 |
| 25   | 20   | 3/4    | 10    | 199 041 131 |     |    | 0.295 |
| 32   | 25   | 1      | 10    | 199 041 132 |     |    | 0.400 |
| 40   | 32   | 1 1/4  | 10    | 199 041 133 |     |    | 0.604 |
| 50   | 40   | 1 1/2  | 10    | 199 041 134 |     |    | 0.943 |
| 63   | 50   | 2      | 10    | 199 041 135 |     |    | 1.930 |
| 75   | 65   | 2 1/2  | 10    | 199 041 136 |     |    | 1.603 |
| 90   | 80   | 3      | 10    | 199 041 137 |     | 1  | 2.570 |


| d    | H    | H1   | L    | L1   | L2   | G1      | G1     | G       | Pouce  |
|------|------|------|------|------|------|---------|--------|---------|--------|
| (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (inch)  | (inch) | (inch)  | (inch) |
| 16   |      | 35   |      | 110  | 40   | R 3/4   |        | R 3/4   | 3/8    |
| 20   |      | 35   |      | 125  | 40   | R 3/4   |        | R 1     | 1/2    |
| 25   |      | 45   |      | 145  | 45   | R 3/4   |        | R 1 1/4 | 3/4    |
| 32   | 96   | 71   | 245  | 195  |      | R 1 1/2 |        | R 1 1/2 | 1      |
| 40   | 116  | 87   | 297  | 239  |      | R 2     |        | R 2     | 1 1/4  |
| 50   | 139  | 105  | 369  | 301  |      | R 2 1/4 |        | R 2 1/4 | 1 1/2  |
| 63   | 169  | 128  | 433  | 351  |      | R 2 3/4 |        | R 2 3/4 | 2      |
| 75   |      | 115  | 388  |      |      |         |        | R 1     | 2 1/2  |
| 90   |      | 149  | 465  |      |      |         |        | R 2 3/4 | 3      |



DN 10 - 20



DN 25 - 50



DN 65 - 80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>