



ecoFIT Segmented Bend 1.5D 30° PE100 SDR9

Model:

- Long spigot for butt- and electrofusion welding
- Application: Water distribution
- Production process: segment welded
- **Derating factor 0.8 as per ISO 4427-3**
- Pressure rating: 16 bar water

Note:

* Please call us for availability

d	Code	Weight	Z	L	R	e
(mm)		(kg)	(mm)	(mm)	(mm)	(mm)
90	P2317604090	0.96	186	150	135.0	10.1
110	P2317604110	1.88	244	200	165.0	12.3
125	P2317604125	2.48	250	200	187.5	14.0
140	P2317604140	3.18	256	200	210.0	15.7
160	P2317604160	4.30	264	200	240.0	17.9
180	P2317604180	5.54	272	200	270.0	20.1
200	P2317604200	7.11	280	200	300.0	22.4
225	P2317604225	9.29	291	200	337.5	25.2
250	P2317604250	13.82	351	250	375.0	27.9
280	P2317604280	18.11	363	250	420.0	31.3
315	P2317604315	30.12	478	350	472.5	35.2
355	P2317604355	39.37	493	350	532.5	39.7
400	P2317604400	51.56	511	350	600.0	44.7
450	P2317604450	67.74	531	350	675.0	50.3
*	500	P2317604500	94.64	601	750.0	55.8
*	560	P2317604560	123.59	625	840.0	62.5
*	630	P2317604630	176.42	703	945.0	70.3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>