




Reducer 電熔大小頭

- 10 bar Gas / 16 bar Water
- 4 mm pin connectors
- Limited path fusion indicators
- Two separate fusion zones



d	d2	DN	PN	code	weight	Do	Lmax	P1	P2	Z1	Z2	SDR pipe
(mm)	(mm)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
200	160	200	16	753 901 837	5,098	250	365	104	90	85,5	85,5	11-26
225	160	200	16	753 901 838	6,000	280	385	112	90	91,5	91,5	11-26
225	200	200	16	753 901 845	8,200	280	390	112	104	86,5	86,5	11-26
250	160	250	16	753 901 840	7,860	310	400	123	90	93,5	93,5	11-26
250	200	250	16	753 901 841	8,480	310	417	123	104	100,0	100,0	11-26
250	225	250	16	753 901 842	8,450	310	430	123	112	102,0	102,0	11-26

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>