




ELGEF Plus Electrofusion coupler PE100 d355-800mm / SDR17

- 5 bar Gas / 10 bar Water
- 4 mm pin connectors
- Limited path fusion indicators
- With active reinforcement
- Ø355 – 500 have two connected (monofilar) welding zones (Both pipe ends can be welded simultaneously)
- Ø560 – 800 have two separate (bifilar) welding zones (Both pipe ends can be welded separately)



d (mm)	DN (mm)	PN (bar)	Code	Weight (kg)	Do (mm)	Lmax (mm)	Suitable for
355	350	10	753 911 804	9.522	416	291	SDR pipe 17 - 33
400	400	10	753 911 805	13.000	467	295	SDR pipe 17 - 33
450	450	10	753 911 806	18.000	526	327	SDR pipe 17 - 33
500	500	10	753 911 807	22.000	584	358	SDR pipe 17 - 41
560	600	10	753 911 808	34.000	647	396	SDR pipe 17 - 41
630	600	10	753 911 809	46.000	727	440	SDR pipe 17 - 41
710	700	10	753 911 810	55.600	820	463	SDR pipe 17 - 41
800	800	10	753 911 811	73.000	922	484	SDR pipe 17 - 41

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>